F80PD DUAL PORT PROFESSIONAL SPREADER





The EV-N-SPRED® Dual Port PRO Adjustable Shut-Off System is included on all Professional models and allows the operator to balance the spread pattern evenly across the full 180° spread width, regardless of the weight or size of granular material. By closing either the right and/or left side throwing ports, you can balance the spread pattern to exacting precision without compromising spread width to application rate.

Engineered for extremely accurate application rates, easy operation and long life, with the EV-N-SPRED® FLEX-SELECT

Interchangeable Tray System,
you can select one of three
optional uniquely suited "trays"
which include precision
engineered apertures and
shut-off systems for
multiple materials
and output rates.
Spread a wide
range of materials
accurately, effectively
and economically.

Low Output

Features

- 36kg Hopper capacity
- EV-N-SPRED® PRO Dual Port Adjustable Shut-Off System
- New "Floating" Super-duty gearbox for long life
- 2-position height adjustable handle for a custom operator fit
- Ergonomic upper handle for easy control
- Tee handle lever & gauge rate control with adjustable solid linkage
- 33cm diameter turf tyres on rust-proof poly rims
- Twin-Tube Professional powder coated chassis
- · Debris screen
- Optional High or Low Input Trays
- 113kg load bearing capacity
- 5-Year Limited Warranty





Standard Output (Included) High Output

