F80SD STAINLESS STEEL DUAL PORT PROFESSIONAL SPREADER





The EV-N-SPRED® Dual Port PRO Adjustable Shut-Off System is included on all Professional models and allows the operator to balance the spread pattern evenly across the full 180° spread width, regardless of the weight or size of granular material. By closing either the right and/or left side throwing ports, you can balance the spread pattern to exacting precision without compromising spread width to application rate.

Engineered for extremely accurate application rates, easy operation and long life, with the EV-N-SPRED® FLEX-SELECT

Interchangeable Tray System, you can select one of three optional uniquely suited "trays" which include precision engineered apertures and shut-off systems for multiple materials and output rates. Spread a wide range of materials accurately, effectively and economically.

Low Output

Standard Output

High Output

Features

- EV-N-SPRED® PRO Dual Port Adjustable Shut-Off System
- 36kg Hopper capacity
- Standard EV-N-SPRED® FLEX-SELECT™
 Dual Port PRO Interchangeable
 Tray included
- New "Floating" Super-duty gearbox for long life
- 2-position height adjustable handle for a custom operator fit
- Ergonomic upper handle for easy control
- Tee handle lever & gauge rate control with adjustable solid linkage
- 113kg load bearing capacity
- 33cm diameter turf tyres on rust-proof poly rims
- Single-tube Commercial Stainless Steel Chassis
- · Debris screen





(Included)

